

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## **7WPCK21B**

Hartland CFX Primed White 1 gang 20AX 2 Way Key Switch Black

Item Image	Wiring	Dimensions	
	Abornable 2 way settling	Hamilton HARTLAND CFX K21 2 Way Key switch	
		66.0	
Primary Range	Hartland CFX		
Insert Type	1 gang 20AX 2 Way Key Switch		
Plate Finish	Hartland CFX Primed White		
Insert Colour	Black		
EAN13 Barcode	5017504015428		
Commodity Code	85363030		
Luckins TSI	398332710		
ETIM Class	EC000029		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	25mm		
Switched Poles	Single		
Current Rating	20AX		
Voltage	220/250V AC		
Maximum Load	20 Amp inductive		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	5 x1mm²		
Terminal Capacity 2	4x1.5mm²		
Terminal Capacity 3	2x2.5mm²		
Terminal Capacity 4	2x4mm² Multi-strand		
Terminal Capacity 5	1x6mm²		
Earth Terminal Capacity 1	6x1mm²		
Earth Terminal Capacity 2	5x1.5mm²		
Earth Terminal Capacity 3	3 x2.5mm²		
Earth Terminal Capacity 4	2x4mm² Multi-strand		
Earth Terminal Capacity 5	1x6mm²		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-1		



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7WPCK21B

Hartland CFX Primed White 1 gang 20AX 2 Way Key Switch Black			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 09:02 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









