Hamilton

## making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio		
7WPCKELB		
Hartland CFX Primed White 1 gang 20AX 2 Way Key switch EMG LTG TEST Black		
Item Image	Wiring	Dimensions
		HARTLAND CFX KEL
		2 Way Key switch EMG LTG TEST
	lotation basister barri∲ y <sub>in</sub> my tarri∲ y <sub>in</sub> my tarright	86.0 5.0
	Alternative 2 way switching intermediate switching	86.0
Primary Range	Hartland CFX	
Insert Type	1 gang 20AX 2 Way Key Switch EMG LTG TEST	
Plate Finish	Hartland CFX Primed White	
Insert Colour	Black	
EAN13 Barcode	5017504015442	
Commodity Code	85363030	
Luckins TSI	398332820	
ETIM Class		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm Single	
Switched Poles	Single 200X	
Current Rating	20AX 220/250V AC	
Voltage	22//2007 AC 20 Amp inductive	
Maximum Load	50Hz	
Mains Frequency	IP2XD	
IP Rating		
Contact Gap Minimum Terminal Capacity 1	3mm 5 x1mm <sup>2</sup>	
Terminal Capacity 1	4x1.5mm <sup>2</sup>	
Terminal Capacity 3	4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup>	
Terminal Capacity 4	2x4mm <sup>2</sup> Multi-strand	
Terminal Capacity 5	1x6mm <sup>2</sup>	
Earth Terminal Capacity 1	6x1mm <sup>2</sup>	
Earth Terminal Capacity 2	5x1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	3 x2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	2x4mm <sup>2</sup> Multi-strand	
Earth Terminal Capacity 5	1x6mm <sup>2</sup>	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	

SL

## Hamilton

## making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio **7WPCKELB** Hartland CFX Primed White 1 gang 20AX 2 Way Key switch EMG LTG TEST Black CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is correct at the time of going to press. as part of our development programme. Therefore, we reserve the right to alter designs BS EN ISO 9001 : 2015 Quality Management System. and dimensions without prior notice. Correct as at 05 July 2022 09:02 AM E&OE Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84



SL