

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7WPCR24BL-B

Hartland CFX Primed White 4 gang 10AX 2 Way Rocker Black/Black

| Item Image                    | Wiring  Wing to the second sec | Dimensions  Hemilton HARTLAND GFX  R24 2 Way Rocker |               |                          |                          |
|-------------------------------|--|---|---------------|--------------------------|--------------------------|
|                               |  |   | Primary Range | Hartland CFX             |                          |
|                               |  |   | Insert Type   | 4 gang 10AX 2 Way Rocker | 4 gang 10AX 2 Way Rocker |
| Plate Finish                  | Hartland CFX Primed White  |   |               |                          |                          |
| Insert Colour                 | Black/Black  |   |               |                          |                          |
| EAN13 Barcode                 | 5017504015602  |   |               |                          |                          |
| Commodity Code                | 85363010   |   |               |                          |                          |
| Luckins TSI                   | 398333117  |   |               |                          |                          |
| ETIM Class                    | EC001590   |   |               |                          |                          |
| Dimensions (Nominal)          | Double: Height = 86.0mm Width = 145.0mm Depth = 5.0  | )mm   |               |                          |                          |
| Fixing Hole Centres           | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |   |               |                          |                          |
| Minimum Wall Box Depth        | 25mm   |   |               |                          |                          |
| Switched Poles                | Single   |   |               |                          |                          |
| Current Rating                | 10AX   |   |               |                          |                          |
| Voltage                       | 220/250V AC  |   |               |                          |                          |
| Maximum Load                  | 10 Amp inductive   |   |               |                          |                          |
| Mains Frequency               | 50Hz   |   |               |                          |                          |
| IP Rating                     | IP2XD  |   |               |                          |                          |
| Contact Gap Minimum           | 3mm  |   |               |                          |                          |
| Terminal Capacity 1           | 5x1mm²   |   |               |                          |                          |
| Terminal Capacity 2           | 4x1.5mm²   |   |               |                          |                          |
| Terminal Capacity 3           | 1x2.5mm²   |   |               |                          |                          |
| Terminal Capacity 4           | 1x4mm² Multi-strand  |   |               |                          |                          |
| Terminal Capacity 5           | 1x6mm²   |   |               |                          |                          |
| Earth Terminal Capacity 1     | 5x1mm²   |   |               |                          |                          |
| Earth Terminal Capacity 2     | 4x1.5mm²   |   |               |                          |                          |
| Earth Terminal Capacity 3     | 3x2.5mm²   |   |               |                          |                          |
| Earth Terminal Capacity 4     | 1x4mm² Multi-strand  | 1x4mm² Multi-strand                                 |               |                          |                          |
| Earth Terminal Capacity 5     | 1x6mm²   |   |               |                          |                          |
| Product Class 1               | Must be earthed  |   |               |                          |                          |
| Ambient Operating Temperature | -5° to +40°C   |   |               |                          |                          |
| Recommended Location          | Internal Use Only  |   |               |                          |                          |
| Maximum Installation Altitude | 2000m  |   |               |                          |                          |
| Standard/Approval             | BS EN 60669-1  |   |               |                          |                          |



making connections beautifully

## Wiring Accessories • Smart Lighting Control • Wireless Audio

## **7WPCR24BL-B**

| Hartland CFX Primed White 4 gang 10AX 2 Way Rocker Black/Black  |   |  |  |
|---|---|--|--|
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 =3023445 |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                               | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  | Correct as at 05 July 2022 09:02 AM<br>E&OE  |  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









