

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7WPCR322BL-B

Hartland CFX Primed White 2 gang 20AX Intermediate Rocker Black/Black

| Item Image                    | Wiring  | Dimensions   |  |  |
|-------------------------------|---|--|--|--|
|                               | 2 Way Switch Switch 2 Way Switch  L1 0 2  L2 1 1 L1  L2 1 L1  Live Live Neutral | Hariano EX R322 Intermediate Rocker                  |  |  |
| Primary Range                 | Hartland CFX  |  |  |  |
| Insert Type                   | 2 gang 20AX Intermediate Rocker   | 2 gang 20AX Intermediate Rocker                      |  |  |
| Plate Finish                  | Hartland CFX Primed White   | Hartland CFX Primed White                            |  |  |
| Insert Colour                 | Black/Black   | Black/Black  |  |  |
| EAN13 Barcode                 | 5017504015688   | 5017504015688  |  |  |
| Commodity Code                | 85363030  | 85363030   |  |  |
| Luckins TSI                   | 398335319   | 398335319  |  |  |
| ETIM Class                    | EC001590  | EC001590   |  |  |
| Dimensions (Nominal)          | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0m                             | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm |  |  |
| Fixing Hole Centres           | Box Fixing = 60.3mm Grid Fixing = CFX Clips                                     | Box Fixing = 60.3mm Grid Fixing = CFX Clips          |  |  |
| Minimum Wall Box Depth        | 25mm  |  |  |  |
| Switched Poles                | Single  |  |  |  |
| Current Rating                | 20AX  |  |  |  |
| Voltage                       | 220/250V AC   |  |  |  |
| Maximum Load                  | 20 Amp inductive  | 20 Amp inductive                                     |  |  |
| Mains Frequency               | 50Hz  |  |  |  |
| IP Rating                     | IP2XD   | IP2XD  |  |  |
| Contact Gap Minimum           | 3mm   |  |  |  |
| Terminal Capacity 1           | 5 x1mm²   |  |  |  |
| Terminal Capacity 2           | 4x1.5mm²  |  |  |  |
| Terminal Capacity 3           | 2x2.5mm²  |  |  |  |
| Terminal Capacity 4           | 2x4mm <sup>2</sup> Multi-strand   | 2x4mm² Multi-strand                                  |  |  |
| Terminal Capacity 5           | 1x6mm²  | 1x6mm²   |  |  |
| Earth Terminal Capacity 1     | 6x1mm²  |  |  |  |
| Earth Terminal Capacity 2     | 5x1.5mm²  |  |  |  |
| Earth Terminal Capacity 3     | 3 x2.5mm²   |  |  |  |
| Earth Terminal Capacity 4     | 2x4mm² Multi-strand   | 2x4mm² Multi-strand                                  |  |  |
| Earth Terminal Capacity 5     | 1x6mm²  |  |  |  |
| Product Class 1               | Must be earthed   |  |  |  |
| Ambient Operating Temperature | -5° to +40°C  |  |  |  |
| Recommended Location          | Internal Use Only   | Internal Use Only                                    |  |  |
| Maximum Installation Altitude | 2000m   |  |  |  |
| Standard/Approval             | BS EN 60669-1   |  |  |  |



making connections beautifully

## Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7WPCR322BL-B

| Hartland CFX Primed White 2 gang 20AX Intermediate Rocker Black/Black   |  |  |  |  |
|---|--|--|--|--|
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 |  |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                          | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |  |
| Illustrations and diagrams are reproduced within  | Due to manufacturing processes we cannot   | Correct as at 05 July 2022 09:02 AM  |  |  |

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









