

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7WPCSS1WH-W

Hartland CFX Primed White 1 gang 13A Double Pole Switched Socket White/White

Primary Rango	Item Image	Wiring	Dimensions	
Insert Type         1 gang 13A Double Pole Switched Socket           Plate Flinish         Hartland CFX Primed White           Insert Colour         White-White           EAN13 Barcode         5017504015848           Commodity Code         85363010           Lickins TSI         38335667           ETIM Class         EC000125           Dimensions (Nominal)         Single: Height = 86.0mm * Width = 86.0mm * Depth = 5.0mm           Weight         148 GR           Fixing Hole Centres         Box Fixing = 60.3mm * Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         200250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         3x4mm²           Terminal Capacity 4         4x2.5mm²           Earth Terminal Capacity 3         3x4mm²           Earth Terminal Capacity 4         1x10mm²           Froduct Class 1 <td< th=""><th></th><th>Earth Live</th><th>SS1 Switched Socket</th></td<>		Earth Live	SS1 Switched Socket	
Plate Finish         Hartland CFX Primed White           Insert Colour         White/White           EAN13 Barcode         S07504015848           Commodity Code         85363010           Luckins TSI         388335607           ETIM Class         EC000125           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         148 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         2020/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           P Rating         IP2D           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         2x6mm²           Terminal Capacity 3         2x6mm²           Terminal Capacity 4         4x2.5mm²           Earth Terminal Capacity 3         2x6mm²           Earth Terminal Capacity 4         4x2.5mm²           Earth Terminal Capacity 3         2x6mm²           Earth Terminal Capacity 4         x10mm²	Primary Range	Hartland CFX		
Insert Colour         White/White           EAN13 Barcode         5017504015848           Commodity Code         85583010           Luckins TSI         398335607           ETIM Class         EC000125           Dimensions (Nominal)         Single Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         148 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Maximum Load         13 Amp           Voltage         19 PX D           Contact Gap Minimum         3mm           19 Pating         IP2XD           Contact Gap Minimum         3mm           1 Ferminal Capacity 1         4x2.5mm²           1 Ferminal Capacity 2         3x4mm²           1 Ferminal Capacity 3         2x6mm² Multi-Strand           1 Earth Terminal Capacity 4         1x10mm²           1 Earth Terminal Capacity 3         2x6mm² Multi-Strand           1 Earth Terminal Capacity 3         2x6mm² Multi-Strand           1 Earth Terminal Capacity 3	Insert Type	1 gang 13A Double Pole Switched Socket		
EAN13 Barcode         5017504015848           Commodity Code         85363010           Luckins TSI         398335607           ETIM Class         EC000125           Dimensions (Nominal)         Single: Helpht = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         148 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Ea	Plate Finish	Hartland CFX Primed White		
Commodity Code         8583010           Luckins TSI         398335607           ETIM Class         EC000125           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         148 GR           Fixing Pole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         200250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x5mm² Multi-Strand           Earth Terminal Capacity 4         4x2.5mm²           Earth Terminal Capacity 3         3x4mm²           Earth Terminal Capacity 4         4x2.5mm²           Earth Terminal Capacity 3         3x4mm²           Earth Terminal Capacity 4         4x2.5mm²           Earth Terminal Capacity 3         3x4mm²           Earth Terminal Capacity 4         4x2.5mm²           Earth Terminal Capacity 4 </td <td>Insert Colour</td> <td colspan="3">White/White</td>	Insert Colour	White/White		
Luckins TSI         398335607           ETIM Class         EC000125           Dimensions (Nomial)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         148 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         20/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         3x4mm²           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         3x4mm²           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         3x4mm²           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4	EAN13 Barcode	5017504015848		
ETIM Class         EC000125           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         148 GR           Kining Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         3x4mm²           Earth Terminal Capacity 4         1x10mm²           Fo to 4dy°C         4x2.5mm²           Risent Operating Temperat	Commodity Code	85363010		
Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         148 GR           Fixing Hole Centres         Box Exing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 5         1x10mm²           Earth Terminal Capacity 6         1x10mm²           Earth Terminal Capacity 7         1x10mm²           Earth Terminal Capacity 8         1x10mm²	Luckins TSI	398335607		
Weight         148 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x5mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           For the Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           For the Capacity 4         1x10mm²           Brance Terminal Capacity 4<	ETIM Class	EC000125		
Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2 5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2 <td>Dimensions (Nominal)</td> <td colspan="3">Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm</td>	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Weight	148 GR		
Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Minimum Wall Box Depth	35mm		
Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Switched Poles	Double		
Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Current Rating	13 Amp		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 4x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-Strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 4x2.5mm² Earth Terminal Capacity 1 4x2.5mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 4 1x10mm² Earth Terminal Capacity 2 3x4mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Earth Terminal Capacity 4 1x10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Voltage	220/250V AC		
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 4x2.5mm²  Terminal Capacity 2 3x4mm²  Terminal Capacity 3 2x6mm² Multi-Strand  Terminal Capacity 4 1x10mm²  Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 3 1x10mm²  Earth Terminal Capacity 4 1x10mm²  Froduct Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Maximum Load	13 Amp		
Contact Gap Minimum  Terminal Capacity 1  4x2.5mm²  Terminal Capacity 2  3x4mm²  Terminal Capacity 3  2x6mm² Multi-Strand  Terminal Capacity 4  1x10mm²  Earth Terminal Capacity 1  Earth Terminal Capacity 2  3x4mm²  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1x10mm²  Earth Terminal Capacity 4  1x10mm²  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 1363-2	Mains Frequency	50Hz		
Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	IP Rating	IP2XD		
Terminal Capacity 2 3x4mm²  Terminal Capacity 3 2x6mm² Multi-Strand  Terminal Capacity 4 1x10mm²  Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 3 1x10mm²  Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Contact Gap Minimum	3mm		
Terminal Capacity 3  Zx6mm² Multi-Strand  1x10mm²  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Zx6mm² Multi-Strand  Earth Terminal Capacity 3  Zx6mm² Multi-Strand  Earth Terminal Capacity 3  Zx6mm² Multi-Strand  Earth Terminal Capacity 4  1x10mm²  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 1363-2	Terminal Capacity 1	4x2.5mm²		
Terminal Capacity 4  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  For to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Internal Use Only  Earth Terminal Capacity 4  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Internal Use Only  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Internal Use Only  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Internal Use Only  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Internal Use Only  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Internal Use Only  Earth Terminal Capacity 4  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Internal Use Only  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7	Terminal Capacity 2	3x4mm²		
Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Terminal Capacity 3	2x6mm² Multi-Strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Cap	Terminal Capacity 4	1x10mm²		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  1x10mm²  Product Class 1  Ambient Operating Temperature  75° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  2x6mm² Multi-Strand  1x10mm²  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  BS 1363-2	Earth Terminal Capacity 1	4x2.5mm <sup>2</sup>		
Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 2	3x4mm²		
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 3	2x6mm² Multi-Strand		
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 4	1x10mm²		
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS 1363-2	Product Class 1	Must be earthed		
Maximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Ambient Operating Temperature	-5° to +40°C	_	
Standard/Approval BS 1363-2	Recommended Location	Internal Use Only		
	Maximum Installation Altitude	2000m		
Additional Nation	Standard/Approval	BS 1363-2		
Additional Notes Dual Earth: Yes	Additional Notes			



making connections beautifully

## Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7WPCSS1WH-W

## Hartland CEX Primed White 1 gang 13A Double Pole Switched Socket White/White

	Hartiand of A Filmed Wille 1 gang 13A Double Fole Switched Socket Wille/Wille			
	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
	All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
	Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 09:03 AM E&OE	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











